

PA-5240 - PA Amplifier



5-zone mono PA mixing amplifier

- 1 x 240 W
- 5 zones, can be controlled individually
- Chime, wailing sound, automatic mute, chime and siren can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs, regulated fan
- Insertions for various functions are available at option
- Phantom power for electret microphones
- Connection for desktop microphone PA-5000PTT
- Alarm announcement with insertion PA-1120DMT (available at option)
- Mains operation and 24 V emergency power operation
- Removable mounting brackets

Tekniske data

| | |
|--|--|
| Peak output power | : 340 W |
| Power rating | : 240 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : 1 x 240 W |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : 240 W |
| Power rating with 4 Ohm bridged operation | : - |
| Power rating with 8 Ohm bridged operation | : - |
| Output impedance | : - |
| Channels | : 5 |
| Zones | : 5 |
| Inputs | : 2.5 mV/2 kOhm (mic 1), 2.5 mV/2 kOhm, 0.3 V/200 kOhm (mic/line 2-4), 0.3 V/5 kOhm (line 5-7), 0.775 V/10 kOhm (preamplifier) |
| Attenuation factor | : - |
| Frequency range | : 55-16,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : ± 10 dB/100 Hz |
| Equalizer midrange | : - |
| Equalizer treble | : ± 10 dB/10 kHz |
| S/N ratio | : ? 70 dB (mic), ? 80 dB (line) |
| Crosstalk attenuation | : - |
| THD | : < 1% |
| Mains voltage | : \sim 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 750 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : DC 24 V |
| Power supply (possible alternative) | : DC 20 A |

Admiss. ambient temp.

: 0-40 °C

Width

: 482 mm

Height

: 133 mm

Depth

: 352 mm





| | |
|-----------------|--|
| Rack spaces, RS | : 3 |
| Weight | : 16 kg |
| Connections | : 2 x 6.3 mm jack (mic), 1 x combo 6.3 mm/XLR (mic/line), 3 x RCA L/R (line), screw terminals (line), 1 x 6.3 mm jack (preamplifier input), screw terminal (push-to-talk mic), screw terminal (zone paging mic), screw terminals |