

# ATT100 - Travel Guide Walkie-Talkie



## Tour guide transmitter

- 10+10 pre-programmed channels, channels 1-10 are transmitting with low power (operating range: approx. 200 m), channels 11-20 are transmitting with increased power (PMR446 standard: high operating range of up to 2 km)
- High battery capacity for continuous announcements of up to 6 hours
- Fully programmable (depending on the application)
- 3 different operating modes can be selected:
  - Continuous transmission
  - Voice control
  - Control via push-to-talk buttons (PTT)
- Matching the tour guide receiver ATR200
- Supplied with belt clip, lanyard

Licence-free, please refer to instruction manual on MONACOR's website.

## Tekniske data

### General information

|                         |                                     |
|-------------------------|-------------------------------------|
|                         | : -                                 |
| Description             | : 20-channel tour guide transmitter |
| Carrier frequency range | : 446.00625-446.1 MHz               |
| Audio frequency range   | : -                                 |
| Channels                | : 20                                |
| THD                     | : -                                 |
| Dynamic range           | : -                                 |
| RF S/N ratio            | : -                                 |
| Operating time          | : -                                 |
| Admiss. ambient temp.   | : -10 °C to +40 °C                  |
| Power supply            | : -                                 |
| Dimensions              | : -                                 |
| Total weight            | : -                                 |
| Connections             | : -                                 |

### Specifications transmitter

|                          |   |
|--------------------------|---|
|                          | : -                                       |
| Transmitting power       | : 10 mW/100 mW                            |
| Operating range          | : 200 m/2 km                              |
| Power supply transmitter | : 1,200 mAh rech. lithium-ion batt.       |
| Width transmitter        | : 83 mm                                   |
| Height transmitter       | : 52 mm                                   |
| Depth transmitter        | : 27 mm                                   |
| Weight transmitter       | : 150 g                                   |
| Connections transmitter  | : 4-pole headset jack, DC charging socket |

|                         |     |
|-------------------------|-----|
| Specifications receiver | : - |
| Audio signal receiver   | : - |
| Power supply receiver   | : - |
| Width receiver          | : - |
| Height receiver         | : - |
| Depth receiver          | : - |
| Weight receiver         | : - |
| Connections receiver    | : - |