


## SP-10/4S - Mini Loudspeaker



Universal speaker, 15 W, 4 Ohm

- Magnetic shielding
- Wide bandwidth speaker of high power capability
- Reproduction from approx. 80 Hz on

## Tekniske data

|   |                     |
|---|---------------------|
| Impedance (Z)                             | : 4 Ohm             |
| Transmission method                       | : -                 |
| Frequency range                           | : f3-8,000 Hz       |
| Resonant frequency (fs)                   | : -                 |
| Rec. crossov. frequ. (fmax.) (12 dB/oct.) | : -                 |
| Power rating (RMS)                        | : 15 W              |
| Peak music power output (MAX)             | : 25 W              |
| Sensitivity                               | : 88 dB/W/m         |
| Max. rated SPL                            | : -                 |
| Max. voltage                              | : -                 |
| Radiation angle, horizontal               | : -                 |
| Radiation angle, vertical                 | : -                 |
| Suspension compl. (Cms)                   | : -                 |
| Moving mass (Mms)                         | : -                 |
| Mech. Q factor (Qms)                      | : -                 |
| Electr. Q factor (Qes)                    | : -                 |
| Total Q factor (Qts)                      | : -                 |
| Equivalent volume (Vas)                   | : -                 |
| DC resistance (Re)                        | : -                 |
| Force factor (BxL)                        | : -                 |
| Voice coil induct. (Le)                   | : -                 |
| Voice coil diameter                       | : -                 |
| Voice coil former                         | : -                 |
| Linear excursion (X <sub>MAX</sub> )      | : -                 |
| Eff. cone area (Sd)                       | : -                 |
| Magnet weight                             | : -                 |
| Magnet diameter                           | : Å~ 77.5 mm        |
| Mounting cutout                           | : Å~ 103 mm         |
| Mounting depth                            | : 63.2 mm           |
| Mounting hole diameter                    | : Å~ 114.5 mm       |
| Hole spacing X-axis                       | : -                 |
| Hole spacing Y-axis                       | : -                 |
| Dimensions                                | : 105 x 105 x 64 mm |
| Outside diameter                          | : -                 |
| Width                                     | : 105 mm            |



|                       |           |
|-----------------------|-----------|
| Height                | : 105 mm  |
| Depth                 | : 64 mm   |
| Protective class      | : -       |
| Admiss. ambient temp. | : 0-40 °C |
| Weight                | : 0.59 kg |
| Packing unit          | : 1       |
| Type of speaker       | : 4"      |