

## HPR-6 - Headphones Amplifier



Efficient stereo headphone amplifier,  
can also be used as a small power amplifier for 4-8 Ohm speaker systems

- Robust metal housing
- Stereo RCA input
- 6.3 mm stereo output
- Volume control and balance control

## Tekniske data

Description	: stereo headphone amplifier
Frequency range	: 19-40,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: 110Â mV-4Â V
Input sensitivity	: -
Input impedance	: -
Output signal	: 2 x 525 mW/2 x 1,500 mW/4 Ohm, 2 x 330 mW/2 x 750 mW/8 Ohm, 2 x 114 mW/2 x 200 mW/32 Ohm
Output impedance	: -
Gain	: -
Phantom power	: -
Compression	: -
Gate ratio	: -
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: 69 dB
Channel separation	: -
THD	: 1%
Admiss. ambient temp.	: 0-40 °C
Power supply	: via encl. plug-in power supply
Dimensions	: 120 x 68 x 36Â mm
Weight	: 288 g
Inputs	: 2 x RCA L/R
Outputs	: 1 x 6.3Â mm jack
Other features	: -