-

Tekniske data

Active/passive	:	passive
Transmission method	:	100 V
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	-
Power rating (RMS)	:	30/15/7.5/4/2Â W
Impedance	:	-
Frequency range	:	40-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	bass-reflex
Full range speaker	:	-
Bass speaker	:	-
Midrange speaker	:	-
Tweeter	:	-
Number of speakers	:	-
Speaker size	:	-
Sensitivity	:	89 dB/W/m
Max. rated SPL	:	103 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	plastic
Colour	:	white
Mounting device	:	pivoting mounting bracket
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	270 x 370 x 220Â mm
Width	:	270 mm
Height	:	370 mm
Depth	:	220 mm
Weight	:	5.4 kg

Inputs	: spring-load. speaker term.
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -