
-

Tekniske data

Active/passive	: active
Transmission method	: -
Total output power	: -
Power rating (RMS)	: 50 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 42-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 720 mV/10 kOhm (bal.) 720 mV/7.7 kOhm (unbal.)
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 16 cm bass speaker
Midrange speaker	: -
Tweeter	: 25 mm soft dome tweeter
Number of speakers	: 2
Speaker size	: 16 cm
Sensitivity	: 86 dB/W/m
Max. rated SPL	: 102 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: MDF wood
Colour	: black
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/120 VA
Dimensions	: 228 x 324 x 295 mm
Width	: 228 mm
Height	: 324 mm
Depth	: 295 mm
Weight	: 7.8 kg

Inputs	: 1 x RCA, unbal., IN (each speaker system) 1 x XLR, bal., IN (each speaker system) 1 x 6.3 mm jack, bal., IN (each speaker system)
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -