

## ESUB-8F/WS - Active Subwoofer



Active subwoofer system, 50 W

- Compact active subwoofer of elegant design as an addition to compact speakers for hi-fi, PA, home cinema and home recording
- Beside volume control, a phase switch and an automatic switch-on, the amplifier also features an adjustable crossover frequency (50-250 Hz)
- High-quality bass-reflex MDF cabinet, high-gloss white
- 20 cm (8") bass speaker
- Inputs via 1 x RCA L/R or screw terminals for high-level L/R
- Parallel line out RCA L/R
- Additional outputs high-level L/R for mid-high range speakers. Thus, well suited for connection to already existing speaker lines
- White fabric front cover

## Tekniske data

|                                |   |
|--------------------------------|---|
| Active/passive                 | : active  |
| Transmission method            | : -   |
| Total output power             | : 90 W  |
| Power rating (RMS)             | : 50 W  |
| Total power rating             | : -   |
| Power rating (RMS)             | : -   |
| Impedance                      | : -   |
| Frequency range                | : 30-250 Hz                                     |
| THD                            | : -   |
| S/N ratio                      | : -   |
| Input signal                   | : 185 mV/9 kOhm (RCA L/R) 4 V/480 Ohm (high IN) |
| System                         | : -   |
| Full range speaker             | : -   |
| Bass speaker                   | : 20 cm (8") bass speaker                       |
| Midrange speaker               | : -   |
| Tweeter                        | : -   |
| Number of speakers             | : 1   |
| Speaker size                   | : 20 cm (8")                                    |
| Sensitivity                    | : 87 dB/W/m                                     |
| Max. rated SPL                 | : 105 dB  |
| Radiation angle, horizontal    | : -   |
| Radiation angle, vertical      | : -   |
| Features                       | : -   |
| Housing material               | : wood  |
| Colour                         | : white, high-gloss                             |
| Mounting device                | : -   |
| Protected against ball rebound | : -   |
| Protection class               | : -   |
| Admiss. ambient temp.          | : 0-40 °C                                       |
| Power supply                   | : &acd; 230 V/50 Hz/152 VA                      |
| Dimensions                     | : 300 x 330 x 340 mm                            |
| Width                          | : 300 mm  |
| Height                         | : 330 mm  |
| Depth                          | : 340 mm  |
| Weight                         | : 9.8 kg  |



|                        |   |
|------------------------|---|
| Inputs                 | : 1 x RCA (L/R), unbal., IN 1 x screw terminals (stereo), high-level IN |
| Outputs                | : 1 x RCA (L/R) 1 x screw terminals (stereo), high-level OUT            |
| Replacement voice coil | : -   |
| Other features         | : -   |
| Accessories            | : -   |