


MRD-80 - Horn Driver



PA horn driver, 30 W, 8 Ohm

- PA tweeter driver with 35 mm (1.38") standard thread
- Very compact size
- High efficiency
- Suitable for horns MRH-83, MRH-170 and MRH-80

Tekniske data

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: fx-17,500 Hz
Resonant frequency (fs)	: 2 kHz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: 5,000 Hz
Power rating (RMS)	: 30 W
Peak music power output (MAX)	: 60 W
Sensitivity	: 107 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: -
Moving mass (Mms)	: -
Mech. Q factor (Qms)	: -
Electr. Q factor (Qes)	: -
Total Q factor (Qts)	: -
Equivalent volume (Vas)	: -
DC resistance (Re)	: -
Force factor (BxL)	: -
Voice coil induct. (Le)	: -
Voice coil diameter	: $\tilde{\sim}$ 25.5 mm
Voice coil former	: -
Linear excursion (X _{MAX})	: -
Eff. cone area (Sd)	: -
Magnet weight	: -
Magnet diameter	: $\tilde{\sim}$ 80 mm
Mounting cutout	: dep. on horn
Mounting depth	: dep. on horn
Mounting hole diameter	: -
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\tilde{\sim}$ 80 mm x 67 mm
Outside diameter	: $\tilde{\sim}$ 80 mm
Width	: $\tilde{\sim}$ 80 mm



Height	: -
Depth	: 67 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 0.71 kg
Packing unit	: 1
Type of speaker	: -