

ATS-12HT - Handheld Transmitter



Hand-held microphone with integrated transmitter

- Matching the 16-channel mono PLL audio transmission system of the ATS-10 series and ATS-16R
- Electret microphone cartridge, cardioid polar pattern
- 16 selectable channels
- Pilot tone
- Mute function
- Push-to-talk function
- Adjustable transmitting power (high: (tm) 10mW/low: (tm) 1 mW)
- Operating range: approx. 50 m
- LCD for indicating channel and battery status
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: Ø 35 mm x 200 mm
- Weight: 93 g

Licence-free in the EU.

Tekniske data

| | |
|-------------------------|--------------------------------------|
| Description | : hand-held microphone transmitter |
| Version | : - |
| Transmission method | : wireless |
| Polar pattern | : cardioid |
| System | : electret |
| Carrier frequency range | : 863-865 MHz |
| Transmitting power | : 10 mW/1 mW |
| Power supply | : 2 x 1.2 V NiMH rech. batt. AA size |
| Operating time | : 12 h/15 h |
| Audio frequency range | : - |
| Nominal impedance | : - |
| Sensitivity | : - |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : ~ 35 mm x 200 mm |
| Weight | : 93 g |
| Cable | : - |
| Connection | : - |