

WALL-08T/WS - PA Speaker Cabinet



Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in white
- 4 power taps as well as switchable to 8 Ohm operation
- 20 cm (8") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Tekniske data

| | |
|--------------------------------|--|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 120 W |
| Power rating (RMS) | : 50/25/12.5/6.25 W (100 V) 60 W (8 Ohm) |
| Impedance | : 8 Ohm |
| Frequency range | : 35-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : 20 cm (8") bass-midrange speaker |
| Midrange speaker | : - |
| Tweeter | : 25 mm (1") dome tweeter |
| Number of speakers | : 2 |
| Speaker size | : 8" |
| Sensitivity | : 90 dB/W/m |
| Max. rated SPL | : 106 dB |
| Beam angle | : - |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : white |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : IP65 |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 245 x 378 x 306 mm (with bracket) |
| Width | : 245 mm |
| Height | : 378 mm |
| Depth | : 306 mm |



| | |
|--------------------------------|----------------------------------|
| Weight | : 5 kg |
| Inputs | : spring-loaded speaker terminal |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : for pivoting and tilting |
| Accessories | : - |
| Packing dimensions (W x H x L) | : - |
| Gross weight | : 13.8 kg |
| Net weight | : 11.8 kg |