

---

-

## Tekniske data

Active/passive	: active
Transmission method	: Cables
Total output power	: 800 W
Power rating (RMS)	: DSP-controlled 400 W (200+200) bass: 200 W mid-high range: 200 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 50-20,000 Hz
THD	: < 0.1%
S/N ratio	: 80 dB
Input signal	: 750 mV/22 kOhm (line), 20 mV/2 kOhm (mic, bal.), 40 mV/2 kOhm (comb.), 200 mV/22 kOhm (aux)
System	: full range
Full range speaker	: -
Bass speaker	: 2 x 20 cm (8")
Midrange speaker	: 12 x 7.6 cm (3")
Tweeter	: 2 x 2.5 cm (1")
Number of speakers	: 16
Speaker size	: 20 cm (8")
Sensitivity	: 95 dB/W/m
Max. rated SPL	: 115 dB at nominal power RMS
Radiation angle, horizontal	: 120°
Radiation angle, vertical	: 30°-90° var.
Features	: -
Housing material	: wood
Colour	: black
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230 V/50 Hz/510 VA
Dimensions	: 250 x 1,730 x 400 mm
Width	: 250 mm
Height	: 1,730 mm

Depth : 400 mm  
Weight : 23 kg

---

Inputs	: 2 x comb. XLR/6.3 mm (line L/R) 1 x comb. XLR/6.3 mm (mic) 1 x comb. XLR/6.3 mm (combo) 1 x RCA (aux L/R) 1 x 3.5 mm jack (aux L/R)
Outputs	: 1 x RCA (rec out, L/R) 1 x XLR, par. out 1 x XLR, MIX out
Replacement voice coil	: -
Other features	: DSP-controlled limiter
Accessories	: -