

MPR-6 - Microphone Pre-Amplifier



Microphone preamplifier,
for connecting up to 2 microphones to one line input.

- Stereo or 2 x mono
- Wide frequency range
- Black metal case
- Supplied with plug-in power supply

Microphone preamplifier,
for connecting up to 2 microphones to a line input of a hi-fi system, an amplifier or a mixer.

- Stereo or 2 x mono
- Wide frequency range
- Black metal case
- Supplied with plug-in power supply

Tekniske data

| | |
|-----------------------|----------------------------------|
| Description | : microphone preamplifier |
| Frequency range | : 5-40,000 Hz |
| Control range | : - |
| Control frequencies | : - |
| Input signal | : 2Â mV/1Â V output |
| Input sensitivity | : - |
| Input impedance | : 10 kOhm |
| Output signal | : max. 3.2Â V/47Â kOhm |
| Output impedance | : - |
| Gain | : 53 dB |
| Phantom power | : - |
| Compression | : - |
| Gate ratio | : - |
| Crossover frequency | : - |
| High-pass filter | : - |
| Low cut | : - |
| Transmission ratio | : - |
| S/N ratio | : 63 dB |
| Channel separation | : - |
| THD | : 0.05% |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : via encl. plug-in power supply |
| Dimensions | : 67 x 37 x 121Â mm |
| Weight | : 215 g |
| Inputs | : 2 x 6.3mm jack |
| Outputs | : 2 x RCA |
| Other features | : - |