


SA-100 - Amplifier

2x50
W_{RMS}



Compact universal stereo amplifier, 50 W

- Silent operation due to fanless cooling concept
- Additional 3.5 mm connection with switchable sensitivity on the front panel
- USB port on the front panel for power supply and for charging external devices
- Audio source selector switch
- Controls for volume, bass and treble
- 6.3 mm headphone output
- Robust metal housing

Tekniske data

Peak output power	: 2 x 50 W
Power rating	: 50 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 25 W
Power rating at 8 Ohm	: 2 x 20 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: -
bridged operation	
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 140 mV/46 kOhm (PC, CD, aux)140 mV/12 kOhm, 25 mV/32 kOhm (player)
Attenuation factor	: -
Frequency range	: 20-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: ± 12 dB
Equalizer midrange	: -
Equalizer treble	: ± 12 dB
S/N ratio	: ? 70 dB
Crosstalk attenuation	: -
THD	: -
Mains voltage	: \sim 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 150 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 212 mm
Height	: 56 mm

Depth

: 250 mm





Rack spaces, RS	: -
Weight	: 2.6 kg
Connections	: 1 x RCA L/R (PC), 1 x RCA L/R (CD), 1 x RCA L/R (aux), 1 x 3.5 mm jack (player), 4 x spring-load. speaker term. (speakers)