

ATT100 - Travel Guide Walkie-Talkie



Tour guide transmitter

- 10+10 pre-programmed channels, channels 1-10 are transmitting with low power (operating range: approx. 200 m), channels 11-20 are transmitting with increased power (PMR446 standard: high operating range of up to 2 km)
- High battery capacity for continuous announcements of up to 6 hours
- Fully programmable (depending on the application)
- 3 different operating modes can be selected:
 - Continuous transmission
 - Voice control
 - Control via push-to-talk buttons (PTT)
- Matching the tour guide receiver ATR200
- Supplied with belt clip, lanyard

Licence-free, please refer to instruction manual on MONACOR's website.

Tekniske data

General information

| | |
|-------------------------|-------------------------------------|
| | : - |
| Description | : 20-channel tour guide transmitter |
| Carrier frequency range | : 446.00625-446.1 MHz |
| Audio frequency range | : - |
| Channels | : 20 |
| THD | : - |
| Dynamic range | : - |
| RF S/N ratio | : - |
| Operating time | : - |
| Admiss. ambient temp. | : -10 °C to +40 °C |
| Power supply | : - |
| Dimensions | : - |
| Total weight | : - |
| Connections | : - |

Specifications transmitter

| | |
|--------------------------|---|
| | : - |
| Transmitting power | : 10 mW/100 mW |
| Operating range | : 200 m/2 km |
| Power supply transmitter | : 1,200 mAh rech. lithium-ion batt. |
| Width transmitter | : 83 mm |
| Height transmitter | : 52 mm |
| Depth transmitter | : 27 mm |
| Weight transmitter | : 150 g |
| Connections transmitter | : 4-pole headset jack, DC charging socket |

| | |
|-------------------------|-----|
| Specifications receiver | : - |
| Audio signal receiver | : - |
| Power supply receiver | : - |
| Width receiver | : - |
| Height receiver | : - |
| Depth receiver | : - |
| Weight receiver | : - |
| Connections receiver | : - |