

## DM-730S - Dynamic Microphone

**new**



Dynamic microphone,  
for vocals (PA, stage, DJ).

- Supercardioid polar pattern
- Neodymium version
- Frequency range: 50-18,000 Hz
- Slide potentiometer
- Diecast zinc body
- Supplied with microphone holder, 9 mm ((tm)) adapter screw and microphone bag

## Tekniske data

|                                |                           |
|--------------------------------|---------------------------|
| Description                    | : vocal microphone        |
| Version                        | : -                       |
| Transmission method            | : cable                   |
| Polar pattern                  | : supercardioid           |
| System                         | : dynamic, neodymium      |
| Carrier frequency range        | : -                       |
| Transmitting power             | : -                       |
| Power supply                   | : -                       |
| Operating time                 | : -                       |
| Audio frequency range          | : 50-18,000 Hz            |
| Nominal impedance              | : 300 Ohm                 |
| Sensitivity                    | : 2.3 mV/Pa               |
| S/N ratio                      | : -                       |
| Max. sound pressure            | : -                       |
| Power supply                   | : -                       |
| Gooseneck length               | : -                       |
| Housing material               | : diecast zinc            |
| Admiss. ambient temp.          | : -                       |
| Dimensions                     | : ~ 48 mm x 182 mm        |
| Weight                         | : 279 g                   |
| Cable                          | : -                       |
| Connection                     | : XLR, bal.               |
| Packing dimensions (W x H x L) | : 0.074 x 0.259 x 0.127 m |
| Gross weight                   | : 0.566 kg                |
| Net weight                     | : 0.350 kg                |