

HSE-150A/SK - Headworn Microphone



Beige-coloured, all-purpose headband microphone for adapter systems. This microphone is comfortable to wear, provides an absolutely secure fit and the high-quality back electret cartridge ensures an excellent audio reproduction of presentations and vocals. Thanks to the omnidirectional polar pattern, even a less than perfectly aligned cartridge is no problem. The flexible connection cable features a plug with latching device to ensure a safe connection with the corresponding adapter. Additional connection adapters for devices from other manufacturers are available at option.

Ultra-light headband microphone

- Omnidirectional polar pattern
- High-quality back electret cartridge
- Plug with latching device
- Supplied with adapters for the TXS-...HSE series (3-pole mini XLR) and pocket transmitters from JTS (4-pole mini XLR)
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Removable sweat-proof connection cable with 2.5 mm stereo plug (replacement connection cable: HSE-70C)
- Optional adapters allow application with devices from other manufacturers
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

Tekniske data

| | |
|-------------------------|--|
| Description | : headband microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : omnidir. |
| System | : back electret |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 20-20,000 Hz |
| Nominal impedance | : 1 kOhm |
| Sensitivity | : 8 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : 130 dB |
| Power supply | : DC 1.5-9 V |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : - |
| Weight | : 7 g |
| Cable | : - |
| Connection | : 2.5 mm stereo plug 2 connection adapters |