NAC-3FX-W-TOP - Powercon inline jack



NEUTRIK POWERCON True1 TOP inline jack

- Complies with safety requirements of IEC 60320, VDE-certified
- For mains connection up to ? 250 V/16 A
- Connections for ground, phase and neutral conductor, connector can be connected under load
- Self-extinguishing according to UL 94V-0
- Protection classs IP65

NEUTRIK

Tekniske data

Description	:	inline jack
Type	:	NEUTRIK POWERCON TOP
Quantity	:	1
Features	:	latching device
Colour/colour coding	:	black
Power rating	:	∿Â 250Â V/16Â A
Insulating resistance	:	? 100 MOhm
Dielectric strength	:	DC 4 kV/∿ 2.8 kV
Certification	:	UL, VDE
Pole number	:	2+PE
Cable inlet	:	6-12 mm
Suitable cable cross section	:	-
Connection	:	-
Strain relief	:	yes
Cable bending protection	:	-
Stereo	:	-
Mono	:	-
Switches	:	-
Material	:	silver-plated bronze contacts, plastic
Central fixing	:	-
Contact type	:	-
No. of contacts	:	-
Contact width	:	-
Contact distance	:	-
Admiss. ambient temp.	:	-30-+80 °C
Dimensions	:	Ã˜ 26.5 mm x 77-80 mm
Diameter	:	-
Length	:	-
Weight	:	33 g
Other features	:	-