
PA-6020Z - PA Amplifier





20-zone mono PA mixing amplifier

- 1 x 600 W
- 20 zones, can be controlled individually
- 3 inputs microphone/line via comb. jacks
- 2 inputs stereo line via RCA jacks
- Chime, continuous sound and wailing sound, automatic mute, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, LEDs for indicating signal/clip, regulated fan
- Insertions for various functions are available at option
- 15 V phantom power for electret microphones
- Connection for up to 3 zone paging microphones PA-2400RC
- Connection for up to 3 push-to-talk microphones PA-4300PTT
- Alarm announcement with insertion PA-1120DMT (available at option)
- Mains operation and 24 V emergency power operation
- Removable mounting brackets

Tekniske data

Peak output power	:	-
Power rating	:	600 W
Power rating at 2 Ohm	:	-
Power rating at 4 Ohm	:	-
Power rating at 8 Ohm	:	-
Power rating at 16 Ohm	:	-
Power rating at 100 V	:	600 W
Power rating with 4 Ohm bridged operation	:	-
Power rating with 8 Ohm bridged operation	:	-
Output impedance	:	-
Channels	:	5
Zones	:	20
Inputs	:	2.5Â mV/5 kOhm, 0.3Â V/5 kOhm (mic/line 1-3), 0.3Â V/15Â kOhm (line 4-5), 0.775Â V/100 kOhm
Attenuation factor	:	-
Frequency range	:	55-16,000 Hz
Crossover network	:	-
Crossover frequency	:	-
Integrated limiter	:	-
Equalizer bass	:	±10Â dB/100Â Hz
Equalizer midrange	:	-
Equalizer treble	:	±10Â dB/10Â kHz
S/N ratio	:	? 70Â dB (mic), ? 80Â dB (line)
Crosstalk attenuation	:	-
THD	:	< 1%
Phantom power	:	15 V
Mains voltage	:	∼ 230 V
Mains frequency	:	50 Hz
Power consumption, operation	:	1,700 VA
Power consumption, standby	:	-
Standby current	:	-
Operating voltage (possible alternative)	:	DC 24 V
Power supply (possible alternative)	:	DC 50 A

Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 133 mm

Depth	:	352 mm
Rack spaces, RS	:	3
Weight	:	21 kg
Connections	:	3 x comb. 6.3 mm/XLR (mic/line), 2 x RCA L/R (line), 1 x 6.3 mm jack (preamplfier input), 1 x RJ45 (push-to-talk mic), 1 x RJ45 (zone paging mic), screw terminals (speakers), 1 x RCA L/R (record output) 1 x 6.3 mm jack (preampli