
WALL-08T/SW - PA Speaker Cabinet





Pair of 2-way PA speaker systems

- 100 V wall speaker with plastic cabinet in black
- 4 power taps as well as switchable to 8 Ohm operation
- 20 cm (8") bass-midrange speaker and 25 mm (1") dome tweeter
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Tekniske data

Active/passive	:	passive
Transmission method	:	100 V
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	120 W
Power rating (RMS)	:	50/25/12.5/6.25Â W (100Â V) 60Â W (8Â Ohm)
Impedance	:	8 Ohm
Frequency range	:	35-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	2-way
Full range speaker	:	-
Bass speaker	:	20 cm (8") bass-midrange speaker
Midrange speaker	:	-
Tweeter	:	25 mm (1") dome tweeter
Number of speakers	:	2
Speaker size	:	8"
Sensitivity	:	90 dB/W/m
Max. rated SPL	:	106 dB
Beam angle	:	-
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	plastic
Colour	:	black
Mounting device	:	mounting bracket
Protected against ball rebound	:	-
Protection class	:	IP65
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	245 x 378 x 306 mm (with bracket)
Width	:	245 mm
Height	:	378 mm
Depth	:	306 mm

Weight	:	5 kg
Inputs	:	spring-loaded speaker terminal
Outputs	:	-
Replacement voice coil	:	-
Other features	:	for pivoting and tilting
Accessories	:	-
Packing dimensions (W x H x L)	:	-
Gross weight	:	13.8 kg
Net weight	:	11.8 kg