

---

-

## Tekniske data

Impedance (Z)	: 8 Ohm
Transmission method	: -
Frequency range	: f3-500 Hz
Resonant frequency (fs)	: 28 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	: -
Power rating (RMS)	: 150 W
Peak music power output (MAX)	: 300 W
Sensitivity	: 93 dB/W/m
Max. rated SPL	: -
Max. voltage	: -
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Suspension compl. (Cms)	: 0.36 mm/N
Moving mass (Mms)	: 78 g
Mech. Q factor (Qms)	: 5.16
Electr. Q factor (Qes)	: 0.34
Total Q factor (Qts)	: 0.32
Equivalent volume (Vas)	: 134 l
DC resistance (Re)	: 6.2 Ohm
Force factor (BxL)	: 15.70 Tm
Voice coil induct. (Le)	: 1.6 mH
Voice coil diameter	: $\varnothing$ 62 mm
Voice coil former	: Kapton
Linear excursion (X <sub>MAX</sub> )	: $\pm$ 8.5 mm
Eff. cone area (Sd)	: 515 cm <sup>2</sup>
Magnet weight	: -
Magnet diameter	: $\varnothing$ 169 mm
Mounting cutout	: $\varnothing$ 282 mm
Mounting depth	: 141.5 mm
Mounting hole diameter	: $\varnothing$ 314 mm
Hole spacing X-axis	: -
Hole spacing Y-axis	: -
Dimensions	: $\varnothing$ 330.5 $\varnothing$ mm x 150 $\varnothing$ mm
Outside diameter	: $\varnothing$ 330.5 mm
Width	: $\varnothing$ 330.5 mm

---

Height	: -
Depth	: 150 mm
Protective class	: -
Admiss. ambient temp.	: 0-40 °C
Weight	: 6.21 kg
Packing unit	: 1
Type of speaker	: 12"