-

Tekniske data

Active/passive	:	passive
Transmission method	:	100 V
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	-
Power rating (RMS)	:	60/30/15 W (100 V) 100 W (8 Ohm)
Impedance	:	8 Ohm
Frequency range	:	110-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	-
Full range speaker	:	8 x Ã˜ 77 mm
Bass speaker	:	-
Midrange speaker	:	-
Tweeter	:	1
Number of speakers	:	9
Speaker size	:	-
Sensitivity	:	95 dB/W/m
Max. rated SPL	:	117 dB
Radiation angle, horizontal	:	70°
Radiation angle, vertical	:	20°
Features	:	-
Housing material	:	aluminium
Colour	:	black
Mounting device	:	wall bracket
Protected against ball rebound	:	-
Protection class	:	IP66
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	125 x 869 x 110 mm
Width	:	125 mm
Height	:	869 mm
Depth	:	110 mm
Weight	:	6 kg

Inputs	: cable
Outputs	: -
Replacement voice coil	: -
Other features	: supplied with wall bracket
Accessories	: -