

PA-912S - PA Amplifier



Mono PA power amplifier

- 1 x 120 W
- Temperature-controlled fan, continuously adjustable
- Protected against overheating, overload and short circuit
- LED indication for clip, protect, overtemperature, output level and 100 V/70 V
- Feed-through output (link)
- Speaker outputs via screw terminals

Tekniske data

| | |
|--|-----------------------------|
| Peak output power | : - |
| Power rating | : 120 W |
| Power rating at 2 Ohm | : - |
| Power rating at 4 Ohm | : - |
| Power rating at 8 Ohm | : - |
| Power rating at 16 Ohm | : - |
| Power rating at 100 V | : 1 x 120 W |
| Power rating with 4 Ohm bridged operation | : - |
| Power rating with 8 Ohm bridged operation | : - |
| Output impedance | : 70 V/40 Ohm, 100 V/80 Ohm |
| Channels | : 1 |
| Zones | : - |
| Inputs | : 670 mV/10 kOhm, balanced |
| Attenuation factor | : - |
| Frequency range | : 80-16,000 Hz |
| Crossover network | : - |
| Crossover frequency | : - |
| Integrated limiter | : - |
| Equalizer bass | : - |
| Equalizer midrange | : - |
| Equalizer treble | : - |
| S/N ratio | : ? 98 dBA |
| Crosstalk attenuation | : - |
| THD | : < 1% |
| Mains voltage | : ~ 230 V |
| Mains frequency | : 50 Hz |
| Power consumption, operation | : 225 VA |
| Power consumption, standby | : - |
| Standby current | : - |
| Operating voltage (possible alternative) | : - |
| Power supply (possible alternative) | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Width | : 483 mm |
| Height | : 44 mm |
| Depth | : 255 mm |

| | |
|-----------------|--|
| Rack spaces, RS | : 1 |
| Weight | : 3.5 kg |
| Connections | : 1 x 6.3 mm/XLR combo (input), 1 x XLR (link), screw terminals (speakers) |