-

Tekniske data

Camera	:	AXC-2812BVM
Design	:	bullet
Image sensor	:	9 mm (1/2.8") CMOS, 2 megapixels
Number of pixels	:	1920 x 1080 pixels max.
Resolution	:	1080p
Lens	:	2.8-12 mm/1:1.2, motorised zoom
Viewing angle	:	35-85°
Min. illumination	:	0 lx with IR illumination
Webserver	:	-
Video streaming	:	-
Compression method	:	-
Protocols	:	-
Protective class	:	IP66
Power supply	:	DCÂ 12 V/480 mA
Operating voltage	:	DC 12 V
Admiss. ambient temp.	:	-20 °C to +50 °C
Dimensions	:	Ã˜ 109 mm x 284 mm
Width	:	Ã˜ 109 mm
Height	:	284 mm
Depth	:	-
Weight	:	350 g
Other features	:	IP66, IR LED, AGC, AWB, DNR
Ethernet	:	-
Audio	:	-
Video	:	TVI, AHD, CVI, CVBS
Video recorder	:	AXR-108
Video inputs	:	8 x BNC
Video outputs	:	1 x HDMIâ„¢ 1 x VGA
Audio inputs	:	8 x RCA
Audio outputs	:	1 x RCA
Resolution	:	1850 x 1080 pixels (25Â fps)
Video compression	:	H.264
Recording	:	200 images/s max.
Menu adjustments	:	on-screen menu (OSD)
Recording mode	:	manual, alarm, timer, motion detector

Search mode	: date and time, event
Lettering	: OSD
Security	: password protection
Video loss detection	: available
Alarm inputs	: 8
Alarm outputs	: 1
Signal device	: integrated
Interfaces	: RS-485, USB 2.0, LAN (RJ45)
Hard disks	: optional, 1 x 8 TB max. (SATA)
Power supply	: DC 12 V/5 A via encl. power supply
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Operating voltage (possible alternative)	: DC 12 V
Power supply (possible alternative)	: DC 5 A
Admiss. ambient temp.	: 0-40 °C
Dimensions	: 300 x 48 x 225 mm
Width	: 300 mm
Height	: 48 mm
Depth	: 225 mm
Weight	: 1.4 kg