

DRUMSET-1 - Microphone Set



7-piece drum microphone set,
consisting of a dynamic bass drum microphone, four dynamic snare drum/tom-tom microphones and two
overhead condenser microphones.

- Optimised for sound pickup of drums
- Short-bodied microphones
- Including microphone holder with 16 mm ((tm)) tripod socket and 9 mm ((tm)) adapter screw for every microphone
- Additional clamps for the snare drum/tom-tom microphones
- Supplied in a practical plastic case

Tekniske data

| | |
|-------------------------|---|
| Description | : drum microphones |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : bi-directional (bass drum) supercardioid (snare drum/tom-tom) cardioid (overhead) |
| System | : dynamic (bass drum) dynamic (snare drum/tom-tom) electret (overhead) |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 50-10,000 Hz (bass drum) 50-15,000 Hz (snare drum/tom-tom) 50-15,000 Hz (overhead) |
| Nominal impedance | : 200 Ohm |
| Sensitivity | : 1.6 mV/Pa (bass drum) 2.5 mV/Pa (snare drum/tom-tom) 5.6 mV/Pa (overhead) |
| S/N ratio | : 66 dB |
| Max. sound pressure | : 158 dB (bass drum) 157 dB (snare drum/tom-tom) 161 dB (overhead) |
| Power supply | : DC 48 V, phantom power (overhead) |
| Gooseneck length | : - |
| Housing material | : - |
| Admiss. ambient temp. | : 0-40 °C |
| Dimensions | : ~ 50 mm x 113 mm (bass drum) ~ 40 mm x 93 mm (snare drum/tom-tom) ~ 22 mm x 90 mm (overhead) 430 x 135 x 320 mm (set) |
| Weight | : 1.5 kg |
| Cable | : - |
| Connection | : XLR, bal. |