-

Tekniske data

Peak output power	: 4,000 W
Power rating	: 2,200 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 1,200 W
Power rating at 8 Ohm	: 2 x 750 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: 1 x 2,200 W
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 1 V/20 kOhm (bal.) 1 V/10 kOhm (unbal.)
Attenuation factor	: -
Frequency range	: 20-20,000 kHz
Crossover network	: DSP
Crossover frequency	: -
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 90 dB
Crosstalk attenuation	: ? 55 dB
THD	: < 0.1%
Mains voltage	: ∼ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 3,400 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 483 mm
Height	: 88 mm

Depth	: 496 mm

Rack spaces, RS	:	2
Weight	:	21 kg
Connections	:	1 x 3-pole XLR L/R, bal. 1 x SPEAKER L/R 1 x SPEAKER (bridged) 1 x USB