-

Tekniske data

Active/passive	:	passive
Transmission method	:	100 V
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	2 x 125 W
Power rating (RMS)	:	60/30/15Â W (100 V) 2 x 60 W (4 Ohm)
Impedance	:	4 Ohm + 4 Ohm
Frequency range	:	50-200 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	-
Full range speaker	:	-
Bass speaker	:	16 cm (6")
Midrange speaker	:	-
Tweeter	:	-
Number of speakers	:	1
Speaker size	:	16 cm (6")
Sensitivity	:	87 dB/W/m
Max. rated SPL	:	108 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	MDF
Colour	:	white
Mounting device	:	wall bracket
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	450 x 350 x 180 mm
Width	:	450 mm
Height	:	350 mm
Depth	:	180 mm
Weight	:	12.25 kg

Inputs	:	Euroblock connector direct Euroblock connector 100Â V
Outputs	:	Euroblock connector satellite
Replacement voice coil	:	-
Other features	:	-
Accessories	:	-