

---

-

## Tekniske data

Peak output power	: 300 W
Power rating	: 200 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 4 x 50 W
Power rating at 8 Ohm	: 4 x 30 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: 2 x 100 W
bridged operation	
Output impedance	: -
Channels	: 4
Zones	: -
Inputs	: 1Â V/20Â kOhm unbal.550Â mV/20Â kOhm bal.
Attenuation factor	: -
Frequency range	: 10-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: -
Crosstalk attenuation	: ? 45 dB
THD	: -
Mains voltage	: ~; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 300 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: ~; 483 mm
Height	: 90 mm

Depth

: 330 mm

---

Rack spaces, RS	: 2
Weight	: 8.4 kg
Connections	: 4 x XLR, bal. 4 x RCA 4 x spring-load. speaker term. L/R