
-

Tekniske data

Peak output power	: 2,100 W
Power rating	: 1,400 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 2 x 700 W
Power rating at 8 Ohm	: 2 x 450 W
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm	: -
bridged operation	
Power rating with 8 Ohm	: 1 x 1,400 W
bridged operation	
Output impedance	: -
Channels	: 2
Zones	: -
Inputs	: 1Â V/20Â kOhm
Attenuation factor	: -
Frequency range	: 20-20,000Â Hz
Crossover network	: 24 dB/oct.
Crossover frequency	: 120 Hz
Integrated limiter	: yes
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 95 dB
Crosstalk attenuation	: ? 60 dB
THD	: < 0.1%
Mains voltage	: ~ 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 2,300 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 482 mm
Height	: 88 mm
Depth	: 418 mm

Rack spaces, RS	: 2
Weight	: 20 kg
Connections	: 1 x 3-pole XLR L/R, bal. 1 x 6.3 mm jack L/R, bal. 1 x NEUTRIK SPEAKON L/R2 x pair of screw terminals