

---

-

## Tekniske data

No. of channels	: -
No. of inputs	: -
Mic input	: 3 mV, bal. (combo jack)
Line input	: 750 mV, bal. (stereo), 100 mV (mono)
CD input	: -
Phono input	: -
Tape (play)	: -
Aux input	: -
Insert input	: 800 mV
Effect return	: -
Master output	: 750 mV, bal. (XLR) 750 mV (jack)
Record output	: -
Monitor output	: -
Booth output	: -
Aux output	: 8 V
Insert output	: 800 mV
Effect send	: -
Control room	: 2.3 V
Tape (rec)	: -
Headphones	: ? 8 Ohm
Gooseneck lamp	: -
WiFi	: -
USB	: yes
<b>Bluetooth</b>	: -
Frequency range	: 20-20,000 Hz
THD	: < 0.01%
S/N ratio	: ? 104 dB
Crosstalk	: ? 80 dB
Equalizer bass	: $\pm 24$ dB/21-19,200 Hz (dep. on filter)
Equalizer midrange	: $\pm 24$ dB/21-19,200 Hz (dep. on filter) $\pm 24$ dB/21-19,200 Hz (dep. on filter)
Equalizer treble	: $\pm 24$ dB/21-19,200 Hz (dep. on filter)
equalizer	: DSP
Talkover	: -
Phantom power	: +48 V
Crossfader	: -

Media player	: -
Amplifier	: -
Power supply	: &acd; 230 V/50 Hz/60 VA
Mains voltage	: &sim; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 60 VA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 442 mm
Height	: 130 mm
Depth	: 355 mm
Rack spaces, RS	: -
Weight	: 7.3 kg