
-

Tekniske data

Description	: compressor/limiter
Frequency range	: 20-20,000 Hz
Control range	: -
Control frequencies	: -
Input signal	: 8.7 V 12.3 V (side chain)
Input sensitivity	: -
Input impedance	: -
Output signal	: 8.7 V
Output impedance	: 60 Ohm bal., 30 Ohm unbal.
Gain	: -
Phantom power	: -
Compression	: 1:1 to ∞:1
Gate ratio	: 1:1.2 to 1:8
Crossover frequency	: -
High-pass filter	: -
Low cut	: -
Transmission ratio	: -
S/N ratio	: ? 90 dB
Channel separation	: ? 100 dB
THD	: < 0.05%
Admiss. ambient temp.	: 0-40 °C
Power supply	: ∿ 230 V/50 Hz/20 VA
Dimensions	: 482 x 44 x 220 mm, 1 RS
Weight	: 3 kg
Inputs	: 2 x XLR, 2 x 6.3 mm jack, 1 x 6.3 mm jack (sidechain)
Outputs	: 2 x XLR, 2 x 6.3 mm jack, 1 x 6.3 mm jack (sidechain)
Other features	: -
Width	: 482 mm
Height	: 44 mm
Depth	: 220 mm
Length	: -
Rack spaces, RS	: 1
Weight	: 3 kg