

# NL4FXX-W-L - Speakon Plug



## NEUTRIK SPEAKON Connectors

Series of Speakon connectors for professional speaker connection technology. Robust design, latching device, all-insulated contacts, cable inlet with self-adjusting clamps.

- Contact resistance: (tm) 2 mOhm
- Current rating: 250 V (music signal)
- Self-extinguishing according to UL 94 V-0

## NEUTRIK SPEAKON plug

- 4-pole screw terminal for litz wires up to 4 mm<sup>2</sup>
- For cables: Ø 10-16 mm

## Tekniske data

|                              |                          |
|------------------------------|--------------------------|
| Description                  | : plug                   |
| Type                         | : NEUTRIK SPEAKON        |
| Quantity                     | : 1                      |
| Features                     | : latching device        |
| Colour/colour coding         | : blue, silver           |
| Power rating                 | : -                      |
| Insulating resistance        | : -                      |
| Dielectric strength          | : -                      |
| Certification                | : UL 94 V-0              |
| Pole number                  | : 4                      |
| Cable inlet                  | : $\tilde{A}$ 10-16 mm   |
| Suitable cable cross section | : 4 mm <sup>2</sup>      |
| Connection                   | : 4-pole screwed contact |
| Strain relief                | : -                      |
| Cable bending protection     | : -                      |
| Stereo                       | : -                      |
| Mono                         | : -                      |
| Switches                     | : -                      |
| Material                     | : -                      |
| Central fixing               | : -                      |
| Contact type                 | : -                      |
| No. of contacts              | : -                      |
| Contact width                | : -                      |
| Contact distance             | : -                      |
| Admiss. ambient temp.        | : -33--+80 °C            |
| Dimensions                   | : -                      |
| Diameter                     | : -                      |
| Length                       | : -                      |
| Weight                       | : 44 g                   |
| Other features               | : IP20                   |