-

Tekniske data

Peak output power	: 45 W
Power rating	: 30 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: 25 W at 24 V 15 W at 12 V
Power rating at 8 Ohm	: 30 W at 24 V 8 W at 12 V
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 1
Zones	: -
Inputs	: 140Â mV/12 kOhm
Attenuation factor	: -
Frequency range	: 10-20,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: -
Equalizer midrange	: -
Equalizer treble	: -
S/N ratio	: ? 100 dBA
Crosstalk attenuation	: -
THD	: < 0.2%
Mains voltage	: -
Mains frequency	: -
Power consumption, operation	: -
Power consumption, standby	: -
Standby current	: 14 mA
Operating voltage (possible alternative)	: -
Power supply (possible alternative)	: -
Admiss. ambient temp.	: 0-40 °C
Width	: 65 mm

Height	: 13 mm
Depth	: 40 mm

Rack spaces, RS	: -
Weight	: 22 g
Connections	: screw terminals