

DM-720S - Dynamic Microphone

new



Dynamic microphone,
for vocals.

- Cardioid polar pattern
- Neodymium version
- Frequency range: 80-12,000 Hz
- Sliding switch
- Diecast zinc body
- Supplied with microphone holder, 9 mm ((tm)) adapter screw and microphone bag

Tekniske data

| | |
|--------------------------------|---------------------------|
| Description | : vocal microphone |
| Version | : - |
| Transmission method | : cable |
| Polar pattern | : cardioid |
| System | : dynamic, neodymium |
| Carrier frequency range | : - |
| Transmitting power | : - |
| Power supply | : - |
| Operating time | : - |
| Audio frequency range | : 80-12,000 Hz |
| Nominal impedance | : 600 Ohm |
| Sensitivity | : 3.1 mV/Pa |
| S/N ratio | : - |
| Max. sound pressure | : - |
| Power supply | : - |
| Gooseneck length | : - |
| Housing material | : diecast zinc |
| Admiss. ambient temp. | : - |
| Dimensions | : ~ 48 mm x 182 mm |
| Weight | : 283 g |
| Cable | : - |
| Connection | : XLR, bal. |
| Packing dimensions (W x H x L) | : 0.074 x 0.259 x 0.127 m |
| Gross weight | : 0.567 kg |
| Net weight | : 0.356 kg |