-

Tekniske data

Active/passive	:	passive
Transmission method	:	-
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	30 W
Power rating (RMS)	:	20 W
Impedance	:	8 Ohm
Frequency range	:	80-22,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	2-way
Full range speaker	:	-
Bass speaker	:	polypropylene bass speaker
Midrange speaker	:	-
Tweeter	:	dome tweeter
Number of speakers	:	2
Speaker size	:	-
Sensitivity	:	87 dB/W/m
Max. rated SPL	:	100 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	ABS plastic
Colour	:	white
Mounting device	:	2 x thread M6
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	150 x 240 x 140 mm
Width	:	150 mm
Height	:	240 mm
Depth	:	140 mm
Weight	:	1.8 kg

Inputs	: speaker screw terminal
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -