-

Tekniske data

Active/passive	:	passive
Transmission method	:	-
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	100 W
Power rating (RMS)	:	60 W
Impedance	:	8 Ohm
Frequency range	:	70-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	2-way bass-reflex
Full range speaker	:	-
Bass speaker	:	2 x 10 cm polypropylene bass speaker
Midrange speaker	:	-
Tweeter	:	dome tweeter
Number of speakers	:	3
Speaker size	:	10 cm
Sensitivity	:	89 dB/W/m
Max. rated SPL	:	-
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	plastic
Colour	:	white
Mounting device	:	mounting bracket
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	150 x 300 x 190Â mm
Width	:	150 mm
Height	:	300 mm
Depth	:	190 mm
Weight	:	3.4 kg

Inputs	: -
Outputs	: -
Replacement voice coil	: -
Other features	: -
Accessories	: -