-

Tekniske data

Peak output power	:	350 W
Power rating	:	225 W
Power rating at 2 Ohm	:	2 x 100 W
Power rating at 4 Ohm	:	2 x 70 W
Power rating at 8 Ohm	:	-
Power rating at 16 Ohm	:	-
Power rating at 100 V	:	-
Power rating with 4 Ohm bridged operation	:	1 x 225 W
Power rating with 8 Ohm bridged operation	:	-
Output impedance	:	-
Channels	:	2
Zones	:	-
Inputs	:	0.4-4Â V/20Â kOhm
Attenuation factor	:	-
Frequency range	:	20-20,000Â Hz
Crossover network	:	-
Crossover frequency	:	40-300 Hz, 6 dB/oct. (low-pass filter) 40-500Â Hz, 6Â dB/oct. (high-pass filter)
Integrated limiter	:	-
Equalizer bass	:	-
Equalizer midrange	:	-
Equalizer treble	:	-
S/N ratio	:	? 94Â dB (A)
Crosstalk attenuation	:	? 45 dB
THD	:	< 0.2%
Mains voltage	:	-
Mains frequency	:	-
Power consumption, operation	:	-
Power consumption, standby	:	-
Standby current	:	-
Operating voltage (possible alternative)	:	DC 12 V
Power supply (possible alternative)	:	22 A
Admiss. ambient temp.	:	0-40 °C
Width	:	252 mm
Height	:	62 mm

Depth	: 243 mm

Rack spaces, RS	:	-
Weight	:	1.91 kg
Connections	:	screw terminals (speakers) 1 x RCA L/R (line in) 1 x RCA L/R (line out)