

## HSE-150A/SK - Headworn Microphone



Beige-coloured, all-purpose headband microphone for adapter systems. This microphone is comfortable to wear, provides an absolutely secure fit and the high-quality back electret cartridge ensures an excellent audio reproduction of presentations and vocals. Thanks to the omnidirectional polar pattern, even a less than perfectly aligned cartridge is no problem. The flexible connection cable features a plug with latching device to ensure a safe connection with the corresponding adapter. Additional connection adapters for devices from other manufacturers are available at option.

Ultra-light headband microphone

- Omnidirectional polar pattern
- High-quality back electret cartridge
- Plug with latching device
- Supplied with adapters for the TXS-...HSE series (3-pole mini XLR) and pocket transmitters from JTS (4-pole mini XLR)
- Turning cartridge arm of adjustable length
- Drip ring (protects cartridge from moisture)
- Removable sweat-proof connection cable with 2.5 mm stereo plug (replacement connection cable: HSE-70C)
- Optional adapters allow application with devices from other manufacturers
- External power supply e.g. via phantom power supply adapter EMA-1 or EMA-300P
- Microphone windshield

## Tekniske data

Description	: headband microphone
Version	: -
Transmission method	: cable
Polar pattern	: omnidir.
System	: back electret
Carrier frequency range	: -
Transmitting power	: -
Power supply	: -
Operating time	: -
Audio frequency range	: 20-20,000 Hz
Nominal impedance	: 1 kOhm
Sensitivity	: 8 mV/Pa
S/N ratio	: -
Max. sound pressure	: 130 dB
Power supply	: DC 1.5-9 V
Gooseneck length	: -
Housing material	: -
Admiss. ambient temp.	: 0-40 °C
Dimensions	: -
Weight	: 7 g
Cable	: -
Connection	: 2.5 mm stereo plug 2 connection adapters