

## TXS-2402SET - Wireless Microphone



With the TXS-2402SET, the entry into the world of digital wireless transmission will become a special sound experience. The signal transmission in the 2.4 GHz range is particularly stable and impresses by a high resistance to interference. The system manages without a compander which results in an incredibly dynamic efficiency and a voice transmission with a unique sound quality. Two systems can be used in parallel operation, thus 4 microphone transmission paths can be used simultaneously. Licence-free system. The particularly easy and convenient use of the units and appealing design make the TXS-2402SET a real digital experience for the user. Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in PSU
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges of supercardioid characteristic

Licence-free in the EU.  
tastenwelt 06/2012

“An entry-level wireless system with a perfectly functioning technology.”

+ Easy operation

+ Well-balanced hand-held transmitter

## Tekniske data

### General information

|                         |                              |
|-------------------------|------------------------------|
|                         | : -                          |
| Description             | : wireless microphone system |
| Carrier frequency range | : 2,404-2,476 MHz            |
| Audio frequency range   | : 80-12,000 Hz               |
| Channels                | : 2                          |
| THD                     | : < 0.1%                     |
| Dynamic range           | : 87 dB                      |
| RF S/N ratio            | : -                          |
| Operating time          | : -                          |
| Admiss. ambient temp.   | : 0-40 °C                    |
| Power supply            | : -                          |
| Dimensions              | : -                          |
| Total weight            | : -                          |
| Connections             | : -                          |

### Specifications transmitter

|                    |  |
|--------------------|--|
|                    | : -  |
| Transmitting power | : 10 mW  |
| Operating range    | : approx. 30 m (free field) approx. 20 m (indoors) |

|                          |                           |
|--------------------------|---------------------------|
| Power supply transmitter | : 2 x 1.5 V batt. AA size |
| Width transmitter        | : 54 mm                   |
| Height transmitter       | : 54 mm                   |
| Depth transmitter        | : 225 mm                  |
| Weight transmitter       | : 120 g                   |
| Connections transmitter  | : -                       |

### Specifications receiver

|                       |                                  |
|-----------------------|----------------------------------|
|                       | : -                              |
| Audio signal receiver | : 100 mV/600 Ohm                 |
| Power supply receiver | : via encl. plug-in power supply |
| Width receiver        | : 220 mm                         |
| Height receiver       | : 45 mm                          |
| Depth receiver        | : 150 mm                         |
| Weight receiver       | : 550 g                          |
| Connections receiver  | : 1 x 6.3 mm jack, unbal.        |