-

Tekniske data

Active/passive	:	passive
Transmission method	:	-
Total output power	:	-
Power rating (RMS)	:	-
Total power rating	:	60 W
Power rating (RMS)	:	30 W
Impedance	:	8 Ohm
Frequency range	:	180-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	-
System	:	full range, closed
Full range speaker	:	8 cm (3")
Bass speaker	:	-
Midrange speaker	:	-
Tweeter	:	-
Number of speakers	:	1
Speaker size	:	8 cm (3")
Sensitivity	:	88 dB/W/m
Max. rated SPL	:	102 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	MDF wood
Colour	:	white
Mounting device	:	mounting bracket
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	-
Dimensions	:	120 x 120 x 105 mm
Width	:	120 mm
Height	:	120 mm
Depth	:	105 mm
Weight	:	0.8 kg

Inputs	: 1 x SPEAKER
Outputs	: 1 x SPEAKER, par. out
Replacement voice coil	: -
Other features	: -
Accessories	: -