

---

-

## Tekniske data

Active/passive	: active
Transmission method	: wireless/cable
Total output power	: 150 W
Power rating (RMS)	: 80 W
Total power rating	: -
Power rating (RMS)	: -
Impedance	: -
Frequency range	: 55-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: 470 mV/10 kOhm (line, XLR, bal.), 1 V/20 kOhm (line, 6.3 mm jack), 500 mV/50 kOhm (line, RCA/3.5 mm jack), 25 mV/10 kOhm (mic, XLR, bal.), 65 mV/20 kOhm (mic, 6.3 mm jack)
System	: 10/2 full range bass-reflex
Full range speaker	: -
Bass speaker	: 25 cm (10") bass speaker
Midrange speaker	: -
Tweeter	: 25 mm (1") horn tweeter
Number of speakers	: 2
Speaker size	: 25 cm (10")
Sensitivity	: 93 dB/W/m
Max. rated SPL	: 113 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: plastic
Colour	: black
Mounting device	: M8 threaded inserts, stand sleeve
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: &acd; 230Â V/50Â Hz/170Â VA
Dimensions	: 320 x 490 x 250Â mm
Width	: 320 mm
Height	: 490 mm
Depth	: 250 mm
Weight	: 8 kg

Inputs	: XLR or 6.3 mm jack (line) RCA L/R or 3.5 mm jack (line) XLR or 6.3 mm jack (mic)
Outputs	: XLR, bal. (mix out)
Replacement voice coil	: -
Other features	: -
Accessories	: -