-

Tekniske data

Active/passive	:	active
Transmission method	:	Cables
Total output power	:	380 W
Power rating (RMS)	:	DSP-controlled 380 W (300+80)bass: 300 Wtreble: 80 W
Total power rating	:	-
Power rating (RMS)	:	-
Impedance	:	-
Frequency range	:	45-20,000 Hz
THD	:	-
S/N ratio	:	-
Input signal	:	375 mV/12 kOhm (line, bal.),3 mV/2.5 kOhm (mic, bal.)
System	:	12/2 full range
Full range speaker	:	-
Bass speaker	:	30 cm (12") bass speaker
Midrange speaker	:	-
Tweeter	:	25 mm (1", 44 mm voice coil) horn tweeter
Number of speakers	:	2
Speaker size	:	30 cm (12")
Sensitivity	:	97 dB/W/m
Max. rated SPL	:	121 dB
Radiation angle, horizontal	:	90°
Radiation angle, vertical	:	60°
Features	:	-
Housing material	:	birch plywood
Colour	:	black
Mounting device	:	M8 threaded inserts, stand sleeve
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	∿ 230Â V/50Â Hz/300 VA
Dimensions	:	350 x 612 x 383 mm
Width	:	350 mm
Height	:	612 mm
Depth	:	383 mm
Weight	:	17.5 kg

Inputs	: 1 x comb. XLR/6.3Â mm: line/mic
Outputs	: 1 x XLR par. out
Replacement voice coil	: -
Other features	: DSP-controlled limiter8 selectable presets
Accessories	: -