-

Tekniske data

Active/passive	:	active
Transmission method	:	Cables
Total output power	:	600 W
Power rating (RMS)	:	300 W
Total power rating	:	-
Power rating (RMS)	:	-
Impedance	:	-
Frequency range	:	35-260 Hz
THD	:	0.208%@5 W/8 Ohm
S/N ratio	:	? 64 dB
Input signal	:	-
System	:	bass-reflex
Full range speaker	:	-
Bass speaker	:	30 cm (12") bass speaker
Midrange speaker	:	-
Tweeter	:	-
Number of speakers	:	1
Speaker size	:	30 cm (12")
Sensitivity	:	96 dB/W/m
Max. rated SPL	:	123 dB
Radiation angle, horizontal	:	-
Radiation angle, vertical	:	-
Features	:	-
Housing material	:	multilayer plywood
Colour	:	black
Mounting device	:	M20 base plate
Protected against ball rebound	:	-
Protection class	:	-
Admiss. ambient temp.	:	0-40 °C
Power supply	:	∿ 230 V/50 Hz/600 VA
Dimensions	:	400 x 475 x 480 mm
Width	:	400 mm
Height	:	475 mm
Depth	:	480 mm
Weight	:	24.7 kg

Inputs	: XLR, bal.
Outputs	: XLR, bal.
Replacement voice coil	: -
Other features	: -
Accessories	: -