

WALL-05T/SW - PA Speaker Cabinet



Pair of 2-way PA speaker systems

- Wall speaker with plastic cabinet in black
- 4 power taps as well as switchable to 8 Ohm operation
- 13 cm (5") bass-midrange speaker and 12 mm (½") dome tweeter
- Suitable for outdoor applications (IP65)
- Weatherproof
- High sound quality and speech intelligibility
- Mounting bracket for pivoting and tilting
- Connecting terminal with cover

Tekniske data

| | |
|--------------------------------|-------------------------------------|
| Active/passive | : passive |
| Transmission method | : 100 V |
| Total output power | : - |
| Power rating (RMS) | : - |
| Total power rating | : 80 W |
| Power rating (RMS) | : 16/8/4/2 W (100 V) 40 W (8 Ohm) |
| Impedance | : 8 Ohm |
| Frequency range | : 80-20,000 Hz |
| THD | : - |
| S/N ratio | : - |
| Input signal | : - |
| System | : 2-way |
| Full range speaker | : - |
| Bass speaker | : 13 cm (5") bass-midrange speaker |
| Midrange speaker | : - |
| Tweeter | : 12 mm (½") dome tweeter |
| Number of speakers | : 2 |
| Speaker size | : 5" |
| Sensitivity | : 89 dB/W/m |
| Max. rated SPL | : 104 dB |
| Radiation angle, horizontal | : - |
| Radiation angle, vertical | : - |
| Features | : - |
| Housing material | : plastic |
| Colour | : black |
| Mounting device | : mounting bracket |
| Protected against ball rebound | : - |
| Protection class | : IP65 |
| Admiss. ambient temp. | : 0-40 °C |
| Power supply | : - |
| Dimensions | : 163 x 252 x 203 mm (with bracket) |
| Width | : 163 mm |
| Height | : 252 mm |
| Depth | : 203 mm |
| Weight | : 2.6 kg |



| | |
|------------------------|------------------------------|
| Inputs | : spring-load. speaker term. |
| Outputs | : - |
| Replacement voice coil | : - |
| Other features | : for pivoting and tilting |
| Accessories | : - |