## [Ausschreibung]

**STA-225**

**Stereo PA amplifier, 700 W,**

with integrated limiter.

• LCD for indicating temperature, operating mode, power
• 2 operating modes can be selected (stereo or bridged)
• Limiter function can be activated as required
• Temperature-controlled fan
• 2 level controls
• Ground lift function
• Speaker switch-on delay
• Protective circuit with LED indication for protection against short circuit and overheating
• Each channel with LEDs for indicating limiter, level and signal

[Technische Daten]:

| | |
|---|---|
| Channels | 2 |
| Power rating | 700 W |
| Power rating at 4 Ω | 2 x 350 W |
| Power rating at 8 Ω | 2 x 250 W |
| Power rating with 8 Ω bridged operation | 1 x 700 W |
| Peak music power output ($P_{MAX}$) | 1,000 W |
| Inputs | 1.3 V/10 kΩ |
| Attenuation factor | |
| Frequency range | 10-50,000 Hz |
| S/N ratio | > 80 dB |
| Crosstalk attenuation | > 50 dB |
| THD | < 0.1% |
| Power supply | ~ 230 V/50 Hz/1,500 VA |
| Mains voltage | ~ 230 V |
| Mains frequency | 50 Hz |
| Power consumption, operation | 1,500 VA |
| Dimensions | 482 x 100 x 330 mm, 2 RS |
| Width | 482 mm |
| Height | 100 mm |
| Depth | 330 mm |
| Rack spaces, RS | 2 |
| Weight | 10.3 kg |
| Connections | 1 x 3-pole XLR L/R, bal.<br>1 x 6.3 mm jack L/R, bal.<br>3 x SPEAKER<br>2 x pair of screw terminals |

Brand: IMG STAGELINE

Type: STA-225

Quantity: 1

Packing dimensions: 0.37 x 0.14 x 0.51 m

Gross weight:

Item weight (w/o accessories):